

SECTION 1: IDENTIFICATION**Product Identifier****Product Form:** Mixture**Product Name:** HELMITHERM 480, HELMITHERM 480C**Intended Use of the Product****Use of the Substance/Mixture:** No use is specified.**Name, Address, and Telephone of the Responsible Party****Company**

Helmitin Inc.

99 Shorncliffe Rd

Toronto, Ontario, M8Z 5K7

877.823.2624

11110 Airport Road

Olive Branch, MS 38654

Phone: 877.823.2624

www.helmitinadhesives.com

Emergency Telephone Number**Emergency Number** : CANUTEC 613-996-6666 / CHEMTREC 1-800-424-9300**SECTION 2: HAZARDS IDENTIFICATION****Classification of the Substance or Mixture****Classification (GHS-US)**

Not Classified

Label Elements**GHS-US Labeling** No labeling applicable**Other Hazards**

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US)

No additional information available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Name	Product Identifier	% (w/w)
Paraffin waxes and Hydrocarbon waxes	(CAS No) 8002-74-2	1 - 5
Distillates, petroleum, steam-cracked, polymerized	(CAS No) 68131-77-1	3 - 7
Quartz*	(CAS No) 14808-60-7	0.1 - 1

*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a solid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES**Description of First Aid Measures****General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.**Skin Contact:** Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

HELMITHERM 480

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Obtain medical attention if irritation persists.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: None expected under normal conditions of use.

Inhalation: May cause respiratory irritation.

Skin Contact: May cause mild skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable.

Explosion Hazard: Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive.

Reactivity: Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing dust. Do not allow contact with incompatible materials (see section 10). Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid. Place spilled material into a container. Avoid actions that cause dust to become airborne.

Methods for Cleaning Up: Clean contaminated surfaces thoroughly. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

HELMITHERM 480

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Good housekeeping is needed during storage, transfer, handling, and use of this material to avoid excessive dust accumulation. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Paraffin waxes and Hydrocarbon waxes (8002-74-2)		
Mexico	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Mexico	OEL STEL (mg/m ³)	6 mg/m ³ (fume)
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (fume)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³ (fume)
Alberta	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
New Brunswick	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Newfoundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Nunavut	OEL STEL (mg/m ³)	6 mg/m ³ (fume)
Nunavut	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Northwest Territories	OEL STEL (mg/m ³)	6 mg/m ³ (fume)
Northwest Territories	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Ontario	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³ (fume)
Québec	VEMP (mg/m ³)	2 mg/m ³ (fume)
Saskatchewan	OEL STEL (mg/m ³)	4 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³
Yukon	OEL STEL (mg/m ³)	6 mg/m ³ (fume)
Yukon	OEL TWA (mg/m ³)	2 mg/m ³ (fume)

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

HELMITHERM 480

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Personal Protective Equipment: Protective clothing. Insufficient ventilation: wear respiratory protection. Gloves. Safety glasses.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: In case of repeated or prolonged contact wear gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink, or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: White (pellets or cartridges)
Odor	: Mild resin odor (when molten)
Odor Threshold	: Not available
pH	: Not applicable
Evaporation Rate	: Not applicable
Melting Point	: 98 -112°C (208 - 234°F) [Ring and Ball Softening Point, ASTM E-28]
Freezing Point	: Not applicable
Boiling Point	: Not applicable
Flash Point	: Not applicable
Auto-ignition Temperature	: Not applicable
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not applicable
Upper Flammable Limit	: Not applicable
Vapor Pressure	: Not applicable
Relative Vapor Density at 20 °C	: Not applicable
Relative Density	: 1.178 g/mL
Specific Gravity	: 1.178 @ 20 °C (68 °F)
Solubility	: Not soluble in water
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: 84,600 mPa.s @ 177 °C (350 °F)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.
VOC Content (SCAQMD Rule 1168)	: 0 g/L (0 lbs/gal)

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

HELMITHERM 480

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: Not classified
Teratogenicity: Not classified
Carcinogenicity: Not classified
Specific Target Organ Toxicity (Repeated Exposure): Not classified
Reproductive Toxicity: Not classified
Specific Target Organ Toxicity (Single Exposure): Not classified
Aspiration Hazard: Not classified
Symptoms/Injuries After Inhalation: May cause respiratory irritation.
Symptoms/Injuries After Skin Contact: None expected under normal conditions of use.
Symptoms/Injuries After Eye Contact: May cause eye irritation.
Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.
Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LD50 Oral Rat	> 3750 mg/kg
LD50 Dermal Rabbit	> 3600 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Not available

Persistence and Degradability Not available

Bioaccumulative Potential

Mobility in Soil

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport

In Accordance with IMDG Not regulated for transport

In Accordance with IATA Not regulated for transport

In Accordance with TDG Not regulated for transport

HELMITHERM 480

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes	
Distillates, petroleum, steam-cracked, polymerized (68131-77-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

Quartz (14808-60-7)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Paraffin waxes and Hydrocarbon waxes (8002-74-2)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
Listed on the Canadian DSL (Domestic Substances List) WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Distillates, petroleum, steam-cracked, polymerized (68131-77-1)	
Listed on the Canadian DSL (Domestic Substances List) WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 08/24/2015
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Helmitin Inc. 99 Shornccliffe Road Toronto, ON, M8Z5K7 T: 877-823-2624 whmis@helmitinadhesives.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.